

APPLICATION FOR UNITED STATES LETTERS PATENT

**METHOD OF MANUFACTURING A BENDING-RESISTANT,
TORSIONALLY YIELDING TUBULAR PROFILED MEMBER AS A
TRANSVERSE SUPPORT FOR A TWIST BEAM REAR AXLE OF A
PASSENGER CAR**

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to a method of manufacturing a bending-resistant, torsionally yielding tubular profiled member as a transverse support for a twist beam rear axle of a passenger car.

2. Description of the Related Art

Various suggestions are known in regard to designs of transverse supports of a twist beam rear axle of a passenger car in order to provide them, on the one hand, with bending resistance and, on the other hand, with a sufficient torsional yield. Prior art references concerned with these problems are, for example, EP 0 249 537 B1, EP 0 681 932 A2, EP 0 752 332 B1, DE-Gm 297 20 207, and U.S. 2,069,911.

All of these transverse supports have in common that their manufacture overall is complex, and, accordingly, the production costs within the context of a complete twist beam rear axle are high.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method of manufacturing a bending-resistant, torsional yielding tubular profiled member as a transverse support for a twist beam rear axle for a passenger car which not only ensures an increased economical production but also, with respect to the respectively required conditions, makes it possible to design the individual process parameters variable as much as possible.

In accordance with the present invention, this is achieved according to a first variant of the method in that a tubular blank of tempering steel is first provided by U-shaped cold forming with a torsionally yielding central longitudinal section while ensuring torsion-proof end sections, whereupon the thus formed tubular profiled member is annealed at least in partial sections thereof at a temperature level between 850° C and 960° C, is subsequently hardened in water at a temperature above the AC3 point, is subsequently tempered at a temperature between 200° C and 550° C for a duration of more than 5 minutes, is subsequently subjected to at least an outer surface hardening, and is finally subjected to further configuration processing steps for completing a twist beam rear axle.

Accordingly, a tube blank, independent of its cross-section, of tempering steel is being used for the manufacture of a tubular profiled member as a transverse support for a twist beam rear axle. First, the tube blank is provided by means of U-shaped cold forming with a central longitudinal section that is torsionally yielding while ensuring at the same time torsion-proof end section. The configuration of the end sections can be as desired. It can be circular or shoe-shaped, optionally with incorporation of stay-shaped sheet metal. Also, reinforcement embossments can be provided in the transitional sections between the U-shaped central longitudinal section and the end sections.

After cold forming, the now present tubular profiled member is subjected to a heat treatment in which, at least in partial sections thereof, it is annealed at a temperature level between 850°C and 960°C. In this context, the term partial sections refers preferably to the end sections of the tubular profiled member. Subsequently, the tubular profiled member is hardened in water at a temperature above the AC3 point of the iron-carbon-diagram and is subsequently tempered at a temperature between 200° C and 550° C for a duration of more than 5 minutes.

A tubular profiled member formed and heat-treated such

exhibits then a high permanent strength under dynamic load, as is desirable especially in regard to the aforementioned torsional profiled member as a component of the twist beam rear axle of a passenger vehicle.

Subsequent to the heat treatment, the tubular profiled member is subjected to at least an outer surface hardening. This refers primarily to a mechanical surface hardening. Optionally, it is also possible to perform an additional inner surface hardening, especially by mechanical means.

Finally, the thus manufactured tubular profiled member is subjected to further configuration processing steps for completion of a twist beam rear axle.

An especially advantageous embodiment of the afore described variant is provided when the tubular profiled member is annealed at a temperature level between 920°C and 950° C, especially approximately 930° C.

In this context it is especially important when the annealed tubular profile is then tempered at a temperature of approximately 280° C for a duration of approximately 20 minutes.

In the context of the invention it is also advantageous when a tube blank of the material specification 22MnB5 is used for the manufacture of the tubular profiled member as a transverse support of a twist beam rear axle.

In accordance with the present invention, the object of the invention is moreover achieved according to a second variant of the method in that a tubular blank of case-hardening steel is first provided by U-shaped cold forming with a torsionally yielding central longitudinal section while ensuring torsion-proof end sections, whereupon the thus formed tubular profiled member is subjected to case hardening at least in partial sections thereof during the course of a heat treatment by carburization of the surface layer of the tubular profiled member with subsequent quenching, is subsequently subjected to at least an outer surface hardening process, and is finally subjected to further configuration processing steps for completion of a twist beam rear axle.

In the context of this variant a case-hardening steel is used. In this variant, a tube blank of a case-hardening steel is also first provided by U-shaped cold forming with a torsionally yielding central longitudinal section. The end sections of the tubular profiled member are, however,

torsion-proof. As in the first variant, the end sections can be of different configurations.

Subsequent to the cold forming step, the thus formed tubular profiled member is case-hardened at least in partial sections thereof during the course of a heat treatment by carburization of the surface layer of the tubular profiled member with subsequent quenching. According to the invention, this also ensures that a cold-formed tubular profiled member as a transverse support in the context of a finished twist beam rear axle is provided with a high permanent strength under dynamic load.

After the heat treatment process an outer surface hardening is carried out. Subsequently, the tubular profiled member is subjected to further configuration processing steps for completion of a twist beam rear axle.

A preferred steel specification (quality) for forming a bending-resistant, torsionally yielding tubular profiled member is C15.

For the first as well as for the second variant of the method according to the invention, it is very advantageous when the heat treatment of the cold-formed tubular profiled

member is performed in the transition sections between the U-shaped central longitudinal section and the torsion-proof end portions.

Moreover, it is advantageous when the surface hardening of the tubular profiled member is carried out by bombarding with balls, especially steel balls.

1. A tubular member having a U-shaped central longitudinal section and torsion-proof end portions, the member being formed by a process in which the surface hardening of the tubular profiled member is carried out by bombarding with balls, especially steel balls.

BRIEF DESCRIPTION OF THE DRAWING

In the drawing:

Fig. 1 is a plan view of a tubular profiled member as a transverse support for a twist beam rear axle of a passenger car;

Fig. 2 is a cross-section of the tubular profiled member according to Fig. 1 along the section line II-II;

Fig. 3 is a cross-section of the tubular profiled member according to Fig. 1 along the section line III-III;

Fig. 4 is a cross-section of the tubular profiled member according to Fig. 1 along the section line IV-IV; and

Fig. 5 is a cross-section of the tubular profiled member according to Fig. 1 along the section line V-V.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In Fig. 1 a tubular profiled member 1 as a transverse support for a twist beam rear axle (known in the art and therefore not explained in more detail in this context) of a passenger car is illustrated. The tubular profiled member 1 is manufactured of an originally round tube blank (Fig. 5) which is comprised of a tempering steel of the steel specification 22MnB5.

The non-cutting cold forming step maintains the cross-section of the tubular profiled member 1 in the end sections. This circular cross-section of the ends 2 of the end sections a of the tubular profiled member 1 has, however, a continuous transition via the transition sections b into a U-shaped double-wall cross-section which extends across the central longitudinal section c of the tubular profiled member 1 (Figs. 1 through 5).

Assuming that the tubular profiled member 1 according to Fig. 1 is illustrated in a plan view, i.e., in the mounted position within the passenger car, the legs 3 of the central U-shaped longitudinal section c (Figs. 2 and 3) extend from an arc-shaped stay 4 in the direction of travel FR with slight divergence relative to the horizontal central

longitudinal plane MLE of the tubular profiled member 1 extending through the longitudinal axis LA.

The tubular profiled member 1 is provided with groove-like embossments 5 at the ends of the central U-shaped longitudinal section c. These embossments 5 extend in a direction transverse to the tubular profiled member 1. Fig. 3 shows that the embossments 5 have the greatest depth at the apex S of the U-shaped longitudinal section c located in the horizontal central longitudinal plane MLE. The depth of the embossments decreases in the direction toward the free ends 6 of the legs 3 until they uniformly adjoin the outer surface 7 of the legs 3. Viewed in longitudinal section, the embossments 5 thus have a sickle-shaped configuration.

The edges 9 of the embossments 5 are rounded.

After cold forming of a circular tube blank of tempering steel of the steel specification (quality) 22MnB5 the now present tubular profiled member 1 according to Figs. 1 through 5 is annealed in the transition sections b at a temperature level of approximately 930° C. Subsequently, the tubular profiled member 1 is hardened in water at a temperature above the AC3 point and is subsequently tempered at a temperature of approximately 280° C for a duration of

20 minutes. Then the tubular profiled member 1 is bombarded with steel balls on its outer surface 10 and is subsequently subjected to further configuration processing steps for completion of a twist beam rear axle.

While specific embodiments of the invention have been shown and described in detail to illustrate the inventive principles, it will be understood that the invention may be embodied otherwise without departing from such principles.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000